



FOR A SAFE ELECTRIC FUTURE.

SMALLER IS SOMETIMES
BIG ENOUGH

NEW



DK 0200



DK 0100

THE NEW ENYCASE DK 0100

The compact entry into the HENSEL world.
With all the advantages of the HENSEL Junction Boxes.

hensel-electric.co.uk

HENSEL

NEW


DK CABLE JUNCTION BOXES – for normal environment and protected outdoor

THE NEW ENYCASE DK 0100



DK 0100 G without terminals

- + dimensions H x W x D: 84 x 84 x 55 mm
- + with integrated elastic membranes, which can be removed for cable entry via cable glands, sealing range Ø 6.0-15.0 mm
- + lid fasteners sealable without accessories
- + external brackets for wall fixing included




rated insulation voltage	$U_i = 1000 \text{ V a.c./d.c.}$
material	PP (polypropylene)



DK 0100 B without terminals

- + dimensions H x W x D: 84 x 84 x 55 mm
- + with integrated elastic membranes, which can be removed for cable entry via cable glands, sealing range Ø 6.0-15.0 mm
- + lid fasteners sealable without accessories
- + external brackets for wall fixing included



rated insulation voltage	$U_i = 1000 \text{ V a.c./d.c.}$
material	PP (polypropylene)



DK 0102 W 0.75-2.5 mm², Cu 3~

- + dimensions H x W x D: 84 x 84 x 55 mm
- + with 5 x Wago 221-413 3-conductor compact terminal
- + per compact terminal 3 x 0.14-4mm² f, 3 x 0.2-4 mm² r
- + with integrated elastic membranes, which can be removed for cable entry via cable glands, sealing range Ø 6.0-15.0 mm
- + lid fasteners sealable without accessories
- + external brackets for wall fixing included



rated insulation voltage	$U_i = 450 \text{ V a.c./d.c.}$
rated current	32 A
material	PP (polypropylene)



DK 0102 X 0.75-2.5 mm², Cu 3~

- + dimensions H x W x D: 84 x 84 x 55 mm
- + with 5 x Wago 221-413 3-conductor compact terminal
- + per compact terminal 3 x 0.14-4mm² f, 3 x 0.2-4 mm² r
- + with integrated elastic membranes, which can be removed for cable entry via cable glands, sealing range Ø 6.0-15.0 mm
- + lid fasteners sealable without accessories
- + external brackets for wall fixing included



rated insulation voltage	$U_i = 450 \text{ V a.c./d.c.}$
rated current	32 A
material	PP (polypropylene)


The right box for every application

In dry, damp, wet or even fire-prone areas –

Cable junction boxes from HENSEL distribute electricity for all areas of application always safe and reliable.



DK series: IP 66
for harsh environmental conditions,
with and without terminals,
elastic membranes or
metric knockouts



RK series: IP 66
with terminal blocks,
elastic membranes



KF series: IP 66 / IP 67 / IP 69
weatherproof, for unprotected
outdoor installation,
with and without terminals,
metric knockouts



WP series: IP 66 / IP 68 / IP 69
submersion up to 20 meters, 168 hours
waterproof, encapsulating for
extreme applications
with terminals,
metric knockouts



FK series: IP 66
E30/E60/E90 intrinsic fire resistance
PH120 insulation integrity
with terminals



KX series: IP 66
for use in potentially explosive
atmospheres
suitable for Ex zone 2 and 22,
with terminals

HENSEL ELECTRIC UK LTD.

Ground Floor
Unit 5
Anglo Office Park
Lincoln Road
High Wycombe
HP12 3FU
United Kingdom
Phone: +44 (0)3450 66 00 55
sales@hensel-electric.co.uk
hensel-electric.co.uk



CONFIGURE YOUR
INDIVIDUAL BOX!

HN MY BOX
Your logo in colour
on the Hensel box